

ANNEXE 6

FLOOR AND TRUSS LOADING OF CONVENTION CENTRE AND EXHIBITION AND EVENT HALLS

Overview of floor load:

Halls:	Maximum floor load:	Type of floor covering
North Hall	3,000 kg/m ²	Asphalt with paint coating
South Hall	3,000 kg/m ²	Asphalt with two-component floating floor
West Hall	3,000 kg/m ²	Latexfalt with paint coat
Congress area ground floor:	Maximum floor load:	Type of floor covering
Lobby	500 kg/m ²	Carpet
Congress area 1st floor:	Maximum floor load:	Type of floor covering
Trajectum	400 kg/m ²	Marble tiles
MECC@Table	400 kg/m ²	Carpet and PVC flooring
Expofoyer	500 kg/m ²	Carpet
Expofoyer terrace	400 kg/m ²	Marble tiles
Forum Passage	500 kg/m ²	Marble tiles
Congress area 2nd floor:		
Promenade	450 kg/m ² with the exception of rooms 350 kg/m ²	Carpet

Overview of truss load:

The overview of the truss load is too complex to fit in a simple matrix. It depends on how the frame is used. MECC Maastricht has appointed a preferred partner for rigging assignments of Hirer, Exhibitor, or Supplier. (At the time of producing this Annexe, Mansveld Expotech is the appointed company.)

Annexe 3 sets out the 'Rigging in the MECC, Guidelines for Riggers' per hall to show the truss loading options.