

ANNEXE 7

STAND TYPES

To help inform exhibitors about the various stand types that are common, this annexe sums up the general types of stands with their specific features in the MECC complex.

Island stands

Island stands are open to gangways on all sides. They must be designed in such a way as to minimize any obstruction of the view of other stands and of the exhibition as a whole. The minimum construction height is 250 cm, including any platforms, and no walls may be erected on the building line. Any requests for exemption should be submitted together with the stand design. Island stands may have ceilings. Free-hanging ceilings (i.e. ceilings suspended entirely from the roof of the building) are permitted once approval has been obtained from the Operations & Facilities department and MECC Maastricht's designated supplier which must attach the suspension wires (see also 'Rigging in the MECC, Guidelines for Riggers', ANNEXE 3).

End stands

End stands are open to gangways on three sides. Such stands should have a back wall. Minimum construction height, including any platforms, is 250 cm.

Corner stands

Corner stands are open to gangways on two sides. They should have a back wall and one side wall. Minimum construction height, including any platforms, is 250 cm.

Interim stands

Interim stands are on one side of a gangway. They must have a back wall and two side walls. Minimum construction height, including any platforms, is 250 cm.

If the construction height of the stand exceeds 250 cm, it must in all cases be approved by way of a stand design by the Project Management department.

In the event of a construction height different from the abovementioned standard height, both the upper and lower stand components must be neatly finished without any advertising.